

“Sample”

The following is a typical pole note that calls for angle or straight mount plumbizer for vehicle or pedestrian signal indications on a vertical pole shaft of a mast arm pole standard:

EB STA 172+38, 32' RT
PA100 POLE FOUNDATION
TYPE PA100-A-50-D40-9 (DAVIT AT 350 DEG)
2-SWING AWAY HINGES
1-ANGLE MOUNT SIGNAL OVERHEAD AT 0'
2-STRAIGHT MOUNT SIGNALS OVERHEAD
AT 11' AND 23'
2-ANGLE MOUNT SIGNALS AT 90 AND 180 DEG
1-ANGLE MOUNT C. D. PED IND AT 180 DEG
1-ONE WAY EVP DETECTOR AND
CONFIRMATORY LIGHT (PHASES 2+5)
LUMINAIRE-250W HPS
1-APS PB AND SIGN (LT ARROW) (PB2-2)
1-SIGN D-A2 ELM ST W
1-SIGN R6-1L ONE WAY
1-SIGN R6-1R ONE WAY
1-SIGN R9-3A NO PED (FACING POLE 2)
3" CONDUIT TO HH 8:
2-12/C #14
1-4/C #14
1-3/C #14
1-3/C #14 LUM
1-2/C #14
1-3/C #20
1-1/C #6 INS. GR.